

TECHNICAL DATA SHEET

PRODUCT NAME – ONYFLOW CI7832

Description:-

ONYFLOW CI 7832, is corrosion Inhibitor available for product pipeline, oil pipe line and other production equipment. It is basically organic amine corrosion Inhibitor forms excellent film on side wall which give protection against the chemical corrosion. It is film forming corrosion inhibitor easily dispersible in water, sea water and brine.

Typical Properties :-

ONY FLOW	ONY FLOW CI7832
COLOUR/ APPEARANCE	CLEAR LIQUID
DENSITY @25°C (ASTM D 298)	0.90-0.96
VISCOSITY (cst @ 40° C) (ASTM D445)	< 20 cst
FLASH POINT('C)(ASTM D93)	68-70°C

Typical dosage in oil field:

A dosage are varying from 3 to 8 PPM, depending on severity of corrosion problem. It normally applies as continuous injection.

Advantage / benefit of Corrosion Inhibitor:-

The ONYFLOW CI 7832 form a high persistence film which gives excellent protection over corrosion. Since it contain Versatile ingredient, is effective at wide range of Ph. (up to Ph 2.0) It is free from Metals and Halogen. It exhibit good dispersion characteristic, and prevent the deposit corrosion.

Packing :-

200 KG Steel drum

INDIA | UAE | USA